

CLAIM AMENDMENT

Please **AMEND** claims 13 and 17, as follows.

Please **ADD** new claims 18-29, as follows.

1-12. (Previously cancelled)

13. (Currently Amended) A display device, comprising :

a mold frame including a series of optical sheets;

a bottom chassis assembled to said mold frame;

a top chassis assembled to said mold frame;

a display panel positioned between said bottom chassis and said top chassis;

a printed circuit board (PCB) connected to said display panel; and

a grounding ~~protrusions~~ protrusion formed on said PCB.

14. (Previously Added) The display device according to claim 13, wherein said mold frame accommodates a lamp assembly and a reflector.

15. (Previously Added) The display device according to claim 14, wherein said display panel is positioned onto said optical sheets.

16. (Previously Added) The display device according to claim 15, wherein said PCB is connected to said display panel via a tape carrier package (TCP), and fixed to said bottom chassis by a fixing means.

17. (Currently Amended) The display device according to claim 16, wherein said grounding ~~protrusions~~ protrusion are formed on said PCB where a signal transmission pattern is not formed.

18. (Currently Added) A display device, comprising:

a chassis;

a display panel assembled with the chassis;

a printed circuit board (PCB) connected to the display panel; and

a ground protrusion formed on a surface of the PCB.

19. (Currently Added) The display device of claim 18, wherein the PCB comprises a grounding pattern, the ground protrusion being protruded from the grounding pattern.

20. (Currently Added) The display device of claim 19, wherein the PCB further comprises a driving integrated circuit (IC) and a signal transmission pattern.

21. (Currently Added) The display device of claim 19, wherein the PCB further comprises a via hole.

21. (Currently Added) The display device of claim 19, wherein the PCB is attached on the chassis.

22. (Currently Added) The display device of claim 21, wherein the PCB has a screw hole and attached to the chassis by a screw.

23. (Currently Added) The display device of claim 22, wherein the screw hole is formed on a corner of the PCB.

24. (Currently Added) The display device of claim 21, wherein the ground protrusion is in direct contact with the chassis.

25. (Currently Added) The display device of claim 18, further comprises a flexible printed circuit board (PCB) coupled between the display panel and the PCB.

26. (Currently Added) The display device of claim 18, further comprises a mold frame assembled with the chassis.

27. (Currently Added) The display device of claim 18, further comprises a backlight assembly unit.

28. (Currently Added) The display device of claim 27, wherein the backlight assembly unit comprises a lamp, a reflector and an optical sheet.

29. (Currently Added) The display device of claim 28, wherein the backlight assembly unit further comprises a light guiding plate.